ITEM	THE ECLIPSE PREMIER	THE TOTAL ECLIPSE	THE SOLAR ECLIPSE	THE ECLIPSE
MODEL HIGHLIGHTS				
Model Description	Ultra premium grade lateral arm	Heavy duty lateral arm	Ultra premium grade cassette style lateral arm	Premium grade lateral arms
When would you select this model	More rugged system with a longer projection option	Very windy situations or for maximum projection	Clean sleek European design	Basic sun protection
Actual customer ratings	4.9 out of 5.0	4.3 out of 5.0	5.0 out of 5.0	4.9 out of 5.0
Unique model features	Conceal arm belt and seal bearing elbows for a quiet and smooth operation	Largest projection lateral arm you can buy in the states	Compact design, semi and full cassette with drop shade option	Cross arm configurations for narrow widths and longer projections
Maximum size (with or without std. aluminum hood)	Up to 40' wide x 13' projection	Up to 40' wide x 16'6" projection	Up to 23' wide x 13' projection	Up to 40' wide x 11'6" projection
Maximum size with semi cassette hood (SC) or full cassette (FC)	SC - Up to 23' wide x 13' Projection	N/A	23' Wide x 13' projection for FC and SC	SC - Up to 22' wide x 11'6" projection

Unit projection range	6'7", 8'2", 10'6", 11'6" & 13'0"	14'9" & 16'6"	8'2", 10'6", 11'6" & 13'0"	5'0", 7'4", 9'0", 10'6" & 11'6"
Mounting options	Wall, soffit & roof			
Standard unit operation	Plug-in motor with override motor feature, remote controlled	Plug in motor with override motor feature, remote controlled	Plug-in motor with override motor feature, remote controlled	Plug-in motor with override motor feature, remote controlled
Width ordering increments	By the 1/4 inch			
Main frame components origin	Spain & USA	Spain & USA	Spain & USA	Spain & USA
Product Assembly	USA	USA	USA	USA
Frame warranty (Non prorated)	Lifetime	Lifetime	Lifetime	10 years
Fabric warranty (Non prorated)	12 years	12 years	12 years	10 years
Platinum protection availability	Included at no additional charge	Included at no additional charge	Included at no additional charge	Yes

Yes

Yes

MODEL OPTIONS

Frame colors	White, Camel, Spartan Bronze & Onyx	White, Camel, Spartan Bronze, Onyx	Alpine & Onyx	White, Camel & Spartan Bronze
Fabric options	100% acrylic Sunbrella shade fabric, 150+ patterns & colors	100% acrylic Sunbrella shade fabric, 150+ patterns & colors	100% acrylic Sunbrella shade fabric, 150+ patterns & colors	100% acrylic Sunbrella shade fabric, 150+ patterns & colors
Front drop shade (motorized or manually operated	Up to 22' wide x 13' projection - Not available with SC	Up to 22' wide x 16'6" projection	Up to 23' wide x 11'6" projection	Up to 22' wide x 11'6" projection
Lighting	Rope lighting or dimmable LED	Rope lighting or dimmable LED	Dimmable LED only	Rope lighting or dimmable LED
Electronic options	Wind sensor, Sun sensor, Rain sensor, Wireless wall switches, Multi channel transmitters, App controlled connectivity	Wind sensor, Sun sensor, Rain sensor, Wireless wall switches, Multi channel transmitters, App controlled connectivity	Wind sensor, Sun sensor, Rain sensor, Wireless wall switches, Multi channel transmitters, App controlled connectivity	Wind sensor, Sun sensor, Rain sensor, Wireless wall switches, Multi channel transmitters, App controlled connectivity

TECHNICAL DATA

10 cable ABT belt system	11 cable ABT belt system	10 cable ABT belt system	9 cable ABT belt system
Cast aluminum, sealed bearings, concealed belt	Cast aluminum, bronze bushings, exposed belt	Cast aluminum, sealed bearings, concealed belt	Cast aluminum, bronze bushings, exposed belt
72,000 cycles	60,000 cycles	72,000 cycles	60,000 cycles
325 Lbs.	400 Lbs.	325 Lbs.	311 Lbs.
920 Lbs.	1800 Lbs.	920 Lbs.	890 Lbs.
Up to class III rated 81 Lbs/30 mph	Up to class III rated 81 Lbs/30 mph	Up to class III rated 81 Lbs/30 mph	Up to class III rated 81 Lbs/30 mph
17 Lbs.	20 Lbs.	22 Lbs.	15 Lbs.
Cast/extruded design - 4Lbs. each	Three piece cast design - 8 Lbs. each	Two piece forged design - 4 Lbs. each	Two piece cast design 3 Lbs. each
1.58" x 1.58" (40mm x 40mm) x .150" Thick - Aluminum	2.00" x 2.00" (50mm x 50mm) x .150" Thick - Aluminum	1.58" x 1.58" (40mm x 40mm) x .150" Thick - Aluminum	1.58" x 1.58" (40mm x 40mm) x .150" Thick - Aluminum
	Cast aluminum, sealed bearings, concealed belt 72,000 cycles 325 Lbs. 920 Lbs. 920 Lbs. Up to class III rated 81 Lbs/30 mph 17 Lbs. Cast/extruded design - 4Lbs. each	Cast aluminum, sealed bearings, concealed beltCast aluminum, bronze bushings, exposed belt72,000 cycles60,000 cycles325 Lbs.400 Lbs.920 Lbs.1800 Lbs.920 Lbs.1800 Lbs.Up to class III rated 81 Lbs/30 mphUp to class III rated 81 Lbs/30 mph17 Lbs.20 Lbs.Cast/extruded design - 4Lbs. eachThree piece cast design - 8 Lbs. each1.58" x 1.58" (40mm x 40mm) x 150"2.00" x 2.00" (50mm x 50mm) x 150"	Cast aluminum, sealed bearings. Cast aluminum, bronze bushings, exposed belt Cast aluminum, sealed bearings, concealed belt 72,000 cycles 60,000 cycles 72,000 cycles 72,000 cycles 325 Lbs. 400 Lbs. 325 Lbs. 325 Lbs. 920 Lbs. 1800 Lbs. 800 Lbs. 920 Lbs. 1y to class III rated 81 Lbs/30 mph Up to class III rated 81 Lbs/30 mph Up to class III rated 81 Lbs/30 mph 17 Lbs. 20 Lbs. 21 Lbs. 22 Lbs. 17 Lbs. 17 the piece cast design - 8 Lbs. each Two piece forged design - 4 Lbs. each 158" x 158" (40mm x 40mm) x 150" 200" x 2.00" (50mm x 50rm) x 150" 158" x 158" (40mm x 40mm) x 150"